


フランジ付き
リニアベアリング

角フランジショートタイプ

無電解ニッケルメッキ付




型式番号	玉列数	主要寸法と許容差													直角度 (最大)	同軸度 (最大)	質量 (kg)	基本定格荷重			
		内径円径		外径		全長		フランジ				取付穴						C (kgf)	Co (kgf)	C (N)	Co (N)
		d (mm)	許容差 (mm)	D (mm)	許容差 (mm)	L (mm)	許容差 (mm)	Df (mm)	W (mm)	T (mm)	PCD (mm)	d1 (mm)	d2 (mm)	h (mm)							
HK-6UU	4	6	0 -0.009	12	0 -0.011	19	0 -0.20	28	22	5	20	3.5	6.0	3.1	0.012	0.012	0.02	21	27	205	264
HK-8UU	4	8		15		24		32	25	5	24	3.5	6.0	3.1			0.03	27	41	264	401
HK-8SUU	4	8		15		17		32	25	5	24	3.5	6.0	3.1			0.024	18	23		
HK-10UU	4	10		19	29	40		30	6	29	4.5	7.5	4.1	0.06			38	56	370	548	
HK-12UU	4	12		21	30	42		32	6	32	4.5	7.5	4.1	0.06			42	61	411	597	
HK-13UU	4	13		23	32	43		34	6	33	4.5	7.5	4.1	0.08			52	79	509	784	
HK-16UU	5	16	0 -0.010	28	0 -0.016	37	0 -0.30	48	37	6	38	4.5	7.5	4.1	0.015	0.015	0.11	79	120	770	1,176
HK-20UU	5	20		32		42		54	42	8	43	5.5	9.0	5.1			0.18	88	140	862	1,372
HK-25UU	6	25		40		59		62	50	8	51	5.5	9.0	5.1			0.30	100	160	983	1,568
HK-30UU	6	30		45	64	74		58	10	60	6.6	11.0	6.1	0.38			160	220	1,568	2,156	
HK-35UU	6	35		52	70	82		64	10	67	6.6	11.0	6.1	0.59			170	320	1,666	3,136	
HK-40UU	6	40		60	80	96		75	13	78	9.0	14.0	8.1	1.21			220	410	2,156	4,018	
HK-50UU	6	50	0 -0.012	80	0 -0.019	100	0 -0.30	116	92	13	98	9.0	14.0	8.1	0.020	0.020	2.00	390	810	3,822	7,938
HK-60UU	6	60		90		110		134	106	18	112	11.0	17.5	10.8			3.20	480	1,020	4,704	9,996

フランジ付き
リニアベアリング

フランジロング (端面タイプ)

無電解ニッケルメッキ付



型式番号	玉列数	主要寸法と許容差												直角度 (最大)	同軸度 (最大)	質量 (kg)	基本定格荷重					
		内径円径		外径		全長		フランジ				取付穴					C (kgf)	Co (kgf)	C (N)	Co (N)		
		d	許容差	D	許容差	L	許容差	Df	W	T	PCD	d1	d2								h	
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)								(mm)	
HK-6LUU	4	6	0 -0.010	12	0	35	0 -0.3	28	22	5	20	3.5	6.0	3.1	0.015	0.015	0.026	33	54	320	529	
HF-6LUU								—	—								0.032					
HK-8LUU	4	8		15	-0.013	45		32	25	5	24	3.5	6.0	3.1			0.040	44	80	428	780	
HF-8LUU								—	—								0.048					
HK-10LUU	4	10		19	55	0		40	30	6	29	4.5	7.5	4.1			0.072	60	112	585	1,097	
HF-10LUU								—	—								0.088					
HK-12LUU	4	12		21	0	57		-0.3	42	32	6	32	4.5	7.5			4.1	0.080	82	159	806	1,560
HF-12LUU									—	—								0.093				
HK-13LUU	4	13		23	-0.016	61		70	43	34	6	33	4.5	7.5			4.1	0.103	83	160	815	1,568
HF-13LUU									—	—								0.118				
HK-16LUU	5	16		28	-0.016	70		80	48	37	6	38	4.5	7.5			4.1	0.148	126	240	1,234	2,352
HF-16LUU									—	—								0.170				
HK-20LUU	5	20	32	0	80	0	54	42	8	43	5.5	9.0	5.1	0.214	143	280	1,401	2,744				
HF-20LUU							—	—						0.247								
HK-25LUU	6	25	40	0	112	0	62	50	8	51	5.5	9.0	5.1	0.472	159	320	1,558	3,136				
HF-25LUU							—	—						0.502								
HK-30LUU	6	30	45	-0.019	123	-0.4	74	58	10	60	6.6	11.0	6.1	0.555	254	560	2,489	5,488				
HF-30LUU							—	—						0.631								

※軸径35以上を使用する場合、お問い合わせ願います。